

**TORO**

# Z Master® 7500-D

## Zero Turn Mower

## FOR A POWERFUL MOWER THAT'S EASY TO OPERATE, CHECK OUT THE TORO Z MASTER® 7500-D.

Looking for a hard-working mower that's easy to operate and gets the job done faster? Check out the Toro® Z Master® 7500-D. Maximum productivity with a 60" (152 cm) or 72" (183 cm) commercial cutting deck. It delivers all the speed and manoeuvrability of a zero-turn, along with the superior quality of cut you expect from Toro.



## FEATURES

### Power & Durability

- Powerful 25 hp or 37 hp Yanmar® EPA Tier 4/Stage V Diesel engines
- Rugged 7-gauge high-strength steel rotary decks
- Rear discharge commercial cutting decks ranging from 60" (152 cm) or 72" (183 cm) width of cut.

### Productivity

- Hydraulic deck lift design with rocker switch for easy cleaning and maintenance
- Up to 20.1 km/h (12.5 mph) ground speed
- 1.0" – 5.5" (2.5 – 14.0 cm) height of cut
- Ride in comfort with the iso-mounted floor pan and deluxe suspension iso-mount seat that dramatically reduce vibration for less operator downtime and more productivity.

### Performance

- Mow smarter with Horizon® Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

### Versatility

- Save on maintenance with extended service intervals

	72028 Horizon® Technology	72029 Horizon Technology	72065 Horizon Technology	72074 Horizon Technology
<b>POWER SYSTEM</b>				
<b>COMMERCIAL ENGINES AT 3600 RPM*</b>	25 hp Yanmar® Diesel 1267cc	25 hp Yanmar Diesel 1267cc	37 hp Yanmar Diesel 1642cc	37 hp Yanmar Diesel 1642cc
<b>HEAVY-DUTY CANISTER AIR CLEANER</b>	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor	Air Filtration System with Electronic Vacuum Sensor
<b>DRIVE TIRES</b>	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")	66,0 x 30,5 x 30,5 cm (26" x 12" – 12")
<b>CASTER TIRES</b>	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic	38,1 x 15,2 x 15,2 cm (15" x 6" – 6") Flat-Free Semi-Pneumatic
<b>FUEL/CAPACITY</b>	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)	Diesel/ 47,3 L (12.5 gal)
<b>HOURLY METER</b>	Horizon Technology	Horizon Technology	Horizon Technology	Horizon Technology
<b>HYDRAULIC DRIVE SYSTEM</b>	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki® Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump	17.84 cu in Hydro-Gear HGM-H Motors with 18 cc Kanzaki Pump
<b>GROUND SPEED</b>	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)	20,1 km/h (12.5 mph)
<b>CLUTCH</b>	Wet Disc	Wet Disc	Wet Disc	Wet Disc
<b>MOWING DECKS</b>				
<b>DECK SIZE</b>	152,4 cm (60") Rear Discharge	182,9 cm (72") Rear Discharge	152,4 cm (60") Rear Discharge	182,9 cm (72") Rear Discharge
<b>CUTTING DECK</b>	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
<b>BULLNOSE BUMPER</b>	Standard	Standard	Standard	Standard
<b>DECK DEPTH</b>	14,0 cm (5.5")	14,0 cm (5.5")	14,0 cm (5.5")	14,0 cm (5.5")
<b>DECK LIFT DESIGN</b>	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch	Hydraulic with Rocker Switch
<b>SPINDLES</b>	9" (22.9 cm) Diameter Cast Aluminum, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminum, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminum, Maintenance-Free	9" (22.9 cm) Diameter Cast Aluminum, Maintenance-Free
<b>HEIGHT OF CUT</b>	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")	2,5 – 14,0 cm (1.0" – 5.5")
<b>BLADES</b>	3 blades at 52 cm (20.5") length	3 blades at 62 cm (24.5") length	3 blades at 52 cm (20.5") length	3 blades at 62 cm (24.5") length
<b>BLADE TIP SPEED</b>	18,200+ ft/min	14,500+ ft/min	18,200+ ft/min	18,500+ ft/min
<b>SHAFT DRIVE</b>	Standard	Standard	Standard	Standard
<b>ANTI-SCALP ROLLERS</b>	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids	4 Standard, 2 Side Skids
<b>FEATURES</b>				
<b>STEERING CONTROLS</b>	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	14,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened	4,1 cm (1-5/8") Dia. Grips; Adjustable, Dampened
<b>OPERATOR SEAT</b>	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)	Deluxe Suspension (Iso-Mount, Flip-Up)
<b>ARM RESTS</b>	Standard	Standard	Standard	Standard
<b>SEAT SUSPENSION SYSTEM</b>	Standard	Standard	Standard	Standard
<b>FOLDING ROPS</b>	Standard	Standard	Standard	Standard
<b>STORAGE COMPARTMENT</b>	Standard	Standard	Standard	Standard
<b>FLOOR PAN</b>	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount	Flip-Up, Iso-Mount
<b>WEIGHTS AND MEASUREMENTS</b>				
<b>WEIGHT<sup>1</sup></b>	887,7 kg (1957 lbs.)	890,9 kg (1964 lbs.)	969 kg (2136 lbs.)	972 kg (2143 lbs.)
<b>ROPS HEIGHT (FOLDED)</b>	129,5 cm (51")	129,5 cm (51")	129,5 cm (51")	129,5 cm (51")
<b>ROPS HEIGHT (UPRIGHT)</b>	182,4 cm (71.8")	182,4 cm (71.8")	182,4 cm (71.8")	182,4 cm (71.8")
<b>DECK CLEARANCE WIDTH</b>	186,4 cm (66.3")	198,9 cm (78.3")	186,4 cm (66.3")	198,9 cm (78.3")
<b>LENGTH</b>	245,1 cm (96.48")	255,7 cm (100.68")	245,1 cm (96.48")	255,7 cm (100.68")
<b>TIER 4 FINAL/STAGE V EMISSION COMPLIANT</b>	Yes	Yes	Yes	Yes
<b>CE KIT REQUIRED</b>	144-0378	144-0410	144-0378	144-0410
<b>WARRANTY</b>	5-Year or 1,200 Hours Limited Warranty; <sup>2</sup> 3-Year Limited Warranty for Engine <sup>3</sup>			
<b>ACCESSORIES</b>	<b>115-4510</b> SUNSHADE – All Z-Masters with ROPS; <b>107-9880</b> Light Kit; <b>107-1630</b> Rubber Striping Kit; <b>135-2473</b> Trash Container Kit; <b>127-6666</b> Jack Kit; <b>135-1768</b> Jack Mount Kit; <b>135-2891</b> Slow Moving Vehicle Kit			

\* The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

\*\* Measured to EN ISO 5395 Lawnmower safety requirements

<sup>1</sup> Net Weight – machine without fuel

<sup>2</sup> Whichever occurs first

<sup>3</sup> Some products used on Toro LCE Products are warranted by the engine manufacturer.