

TORO

Z Master® 4000

Zero Turn Mower

WHEN TAKING ON NATURE, THE Z-MASTER 4000 SERIES IS A POWERHOUSE.

Constructed with military grade materials and the Turbo Force® cutting deck with bullnose bumper, and pro-grade engines, loaded with a heavy-duty front-end design. Mow in comfort with standard electronic deck lift assist, front step-thru deck, USB ports and optional MyRIDE® suspension seat system.



Powered by
Kawasaki



FEATURES

Power & Durability

- Powerful 16,4 kW (22 HP) Kawasaki FX691V or 19 kW (25.5 HP) Kawasaki FX801V EU Stage V compliant engines
- Fully tubular frame and rugged 7-gauge TURBO FORCE® decks
- Available 122 cm (48"), 132 cm (52") or 152 cm (60") width of cut.

Performance

- 74048TE - 19,500 m²/hr (4.8 acres/hr)
- 74053TE - 25,500 m²/hr (6.3 acres/hr)
- 74056TE - 30,000 m²/hr (6.3 acres/hr)

Productivity

- Electric Deck Lift Assist tilt-up deck for ease of use during option. On select models.
- Up to 19 kph (12 mph) ground speed**
- 3,8-14 cm (1.5-5.5") height of cut with the standard mechanical Height of Cut foot pedal
- MyRIDE® platform
- Built-in LED light gives you a superb view in dark conditions. Select models.

Versatility

- Quick Carry System, No-Tools Trimmer Mount Kit sold separately.

*Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.

**The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

	74048TE Pro Base MyRIDE®	74053TE HDX MyRIDE	74056TE HDX MyRIDE
POWER SYSTEM			
ENGINE	22 HP Kawasaki FX691V 726 cc	25.5 HP Kawasaki FX801V 852 cc	25.5 HP Kawasaki FX801V 852 cc
STARTER	Electric	Electric	Electric
HEAVY-DUTY DONALDSON® CANISTER AIR CLEANER	Standard	Standard	Standard
CE COMPLIANT	Yes	Yes	Yes
DRIVE TIRES	Super Turf 61 cm x 24 cm - 30,5 cm (24" x 9.5"-12")	Voodoo 66 cm x 26,7 cm - 30,5 cm (26" x 10.5"-12")	Voodoo 66 cm x 30,5 cm - 30,5 cm (26" x 12"-12")
CASTER TIRES	Black Pneumatic 33 cm x 16,5 cm x 15,2 cm (13" x 6.5" x 6")	Black Pneumatic 33 cm x 16,5 cm x 15,2 cm (13" x 6.5" x 6")	Black Pneumatic 33 cm x 16,5 cm x 15,2 cm (13" x 6.5" x 6")
FUEL/CAPACITY	Petrol 37,8 L (10 gal)	Petrol 37,8 L (10 gal)	Petrol 37,8 L (10 gal)
DIGITAL HOUR METER & USB PORT	Standard	Standard	Standard
HYDRAULIC DRIVE SYSTEM	Integrated Pumps & Wheel Motors	Integrated Pumps & Wheel Motors	Integrated Pumps & Wheel Motors
GROUND SPEED	16 kph (10 mph)	19 kph (12 mph)	19 kph (12 mph)
MOWING DECKS			
DECK SIZE	122 cm (48")	132 cm (52")	152 cm (60")
DECK CONSTRUCTION	7-ga TURBO FORCE®, Side Discharge	7-ga TURBO FORCE®, Side Discharge	7-ga TURBO FORCE®, Side Discharge
BULLNOSE BUMPER	Standard	Standard	Standard
RUBBER DISCHARGE CHUTE	Standard	Standard	Standard
BULLNOSE BUMPER	Standard	Standard	Standard
SPINDLE ASSEMBLIES	22,9 cm (9") Diameter Die-Cast Aluminum, Maintenance Free	22,9 cm (9") Diameter Die-Cast Aluminum, Maintenance Free	22,9 cm (9") Diameter Die-Cast Aluminum, Maintenance Free
HEIGHT OF CUT	3,8-14 cm (1.5-5.5"), 0,64 cm (0.25") increments	3,8-14 cm (1.5-5.5"), 0,64 cm (0.25") increments	3,8-14 cm (1.5-5.5"), 0,64 cm (0.25") increments
HEIGHT OF CUT FOOT PEDAL	Mechanical, Foot Operated	Electric	Electric
DECK DEPTH	14 cm (5.5")	14 cm (5.5")	14 cm (5.5")
BLADES	3 Blades; 0,52 cm (0.204")	3 Blades; 0,52 cm (0.204")	3 Blades; 0,52 cm (0.204")
FEATURES			
MyRIDE® SUSPENSION SYSTEM	Yes	Yes	Yes
SHOCKS	NA	1 center / 2 rear	1 center / 2 rear
SEAT	Deluxe w/ Armrests	Deluxe w/ Armrests	Deluxe w/ Armrests
STEERING CONTROLS	3,6 cm (1.4") Diameter Grips; Adjustable, Dampened	3,6 cm (1.4") Diameter Grips; Adjustable, Dampened	3,6 cm (1.4") Diameter Grips; Adjustable, Dampened
OPERATOR SEAT	High-Back Comfort	High-Back Comfort	High-Back Comfort
ROPS	Square Tube	Square Tube	Square Tube
LED LIGHTS	Optional	Standard	Standard
STEP THROUGH FLOORPAN	Standard	Standard	Standard
ELECTRIC DECK LIFT ASSIST	Optional	Standard	Standard
WEIGHT & MEASUREMENTS			
WEIGHT¹	517 kg (1140 lbs)	582 kg (1284 lbs)	543 kg (1197 lbs)
ROPS HEIGHT (UPRIGHT)	182 cm (71.7")	185,7 cm (73.1")	185,7 cm (73.1")
ROPS HEIGHT (FOLDED)			
WIDTH (DEFLECTOR DOWN)	160,5cm (63.2")	171 cm (67.3")	191 cm (75.3")
WIDTH (DEFLECTOR UP)	132,6 cm (52.2")	141,5 cm (55.7")	156,5 cm (61.6")
LENGTH	220 cm (86.6")	220 cm (86.6")	220 cm (86.6")
TIER 4 FINAL/STAGE V EMISSION COMPLIANT	Yes	Yes	Yes
WARRANTY	5-Years or 1250 hours. ² 2-Year Limited Warranty for Engine. ³		
ACCESSORIES	78463 Bagger Kit; 78464 48" Completion Kit; 78465 52" Completion Kit; 78466 60" Completion Kit; 144-0386 Recycler Kits – 122 cm (48"); 144-0387 Recycler Kits – 132 cm (52"); 144-0388 Recycler Kits – 152 cc (60"); 144-2665 Trimmer Mount Kit (no-tools); 144-0389 Base Light Kit; 144-0390 Electric Deck Lift Kit; 126-7882 Striping Kit		

* The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

** Measured to EN ISO 5395 Lawnmower safety requirements

¹ Net Weight – machine without fuel

² Whichever occurs first

³ Some products used on Toro LCE Products are warranted by the engine manufacturer.

toro.com

©2020 The Toro Company.
All Rights Reserved.
20-612-GB

Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

